



Hydraulic® HFC

Mining > HYDRAULIC FLUIDS

GENERAL INFORMATION

Fire-resistant hydraulic fluid of HFC type. It is intended for use in hydraulic systems of machines and devices operating in particularly dangerous conditions, where there is a risk of fire.

PROPERTIES

Hydraulic® HFC is an aqueous solution of polymers and functional additives such as lubricants, corrosion inhibitors and anti-foaming agents. The product meets the criteria of the 7th Luxembourg Report and the EN-ISO 12922:2002 standard. Thanks to its appropriately selected composition, it has excellent lubricating and anti-wear properties. It does not cause corrosion of steel, copper, brass, aluminum and zinc. The presence of appropriate anti-foaming agents minimizes the risk of cavitation. It is not a hazardous product according to the REACH regulation and is easily biodegradable. It does not contain nitrites, nitrosamines, diethanolamine.

Characteristics - typical properties:

Appearance: clear red liquid

Density at 20°C: 1.14 g/cm³

pH: 8.8

Viscosity at 40°C: 46 mm²/s

Water content: 39% (m/m)

APPLICATION

It is intended for use in hydraulic systems of machines and devices operating in particularly hazardous conditions, wherever the use of oil-based hydraulic fluids is unacceptable due to the risk of fire or explosion. i.e. in the following industries:

- mining and coking, e.g. roadheaders and longwall shearers, loaders, wall conveyors
- steel, e.g. hydraulic systems of heat treatment furnaces
- foundry, e.g. in pressure casting machines
- metallurgical, e.g. in hydraulic presses for metalworking
- forging, e.g. in hydraulic forging presses
- construction, e.g. in tunnel boring machines
- automotive, e.g. in pressure washers
- plastics, e.g. in hydraulic injection molding systems
- and many others.

The information contained in this document is provided in good faith, based on our current knowledge and experience. We reserve the right to make changes as a result of technological progress and product improvements by the manufacturer. The suitability of the product for the intended use should be verified before use. All information, including technical support, is provided without any warranty and may change without notice. The parties explicitly agree that the customer accepts and explicitly releases us from all tortious, contractual or other liability for events arising in connection with the use of our products, information and technical support. Nothing in this document may be construed as a recommendation to use the products in a manner contrary to patent claims regarding materials or methods of use.